

Double Shaft Room Air Conditioner Motors

PSC, 48 Frame, Open Air Over

Applications:

- Air conditioners, double blowers
- May be used as replacements on air conditioners manufactured by Chrysler, Sears, Whirlpool, Gibson, Quiet Kool, Carrier, Fedders, York and others

Features:

- 60 Hz
- Thermally protected
- Shaft: flatted on both extensions
- Studs: four on both ends of motor, 5-3/16" centers
- Capacitor not included

Order #	Mfg. #	Diam.	HP	Volts	RPM	Speeds	F/L Amps	Efficiency	Shaft Diam.	Shaft Length	Rot.	"A" Dim.	Bearing Type	Wt. Lbs.	Capacitor To Match	Each
S88-307	SA1016	5-5/8"	1/6-1/10	208-230	1075	3	0.96	65.0%	1/2"	8-1/4" x 8"	Dbl. Shaft	3-3/4"	Slv	10.6	G21-930	315.00
S88-308	SA1026	5-5/8"	1/4-1/8	208-230	1075	3	1.50	65.0%	1/2"	7-9/10" x 8"	Dbl. Shaft	4-1/8"	Slv	13.8	G21-930	339.00
S88-309	SA1036V1	5-5/8"	1/3-1/6	208-230	1075	3	2.20	65.0%	1/2"	8"	Dbl. Shaft	4-1/8"	Slv	12.5	G21-930	365.00
S88-306	399A	5-5/8"	1/3-1/5	230	1365	3	2.70	65.0%	1/2"	7-1/2" x 7-3/4"	Dbl. Shaft	4-1/2"	Slv	14.2	G21-930	505.00



Double Shaft Fan and Blower Motors

PSC, 48 Frame, Open Air Over

NEW

- Single-phase, 1625 or 1075 RPM, sleeve bearing "Conservationist" energy-efficient design

Applications:


- Can be used in a variety of commercial and residential air conditioners, furnaces, air handlers, unit heaters and similar air over applications

Features:

- Quiet sleeve bearings in heavy diecast end bell

- 3-speed
- Automatic reset thermal overload protector
- Long double shafts, extended thru-bolts
- Packed with a heavy-duty length adapter kit which includes a ring bracket
- 2-1/4" resilient rings, split rings for conversion to 2-1/2" and necessary hardware
- Provision for mounting capacitors (capacitors and strap not included)

Order #	Mfg. #	Diam.	HP	Volts	RPM	Speeds	F/L Amps	Efficiency	Shaft Diam.	Shaft Length	Rot.	Bearing Type	Wt. Lbs.	Capacitor To Match	Each
S88-348	RAL1006	5-5/8"	1/8	115	1075	3	2.00	65.0%	1/2"	8-5/16" x 7-9/16"	Dbl. Shaft	Slv	11.0	G21-930	395.00
S88-349	RA1006	5-5/8"	1/8	208-230	1075	3	0.75	65.0%	1/2"	8-5/16" x 7-9/16"	Dbl. Shaft	Slv	11.2	G21-930	405.00
S88-350	RAL1016	5-5/8"	1/6	115	1075	3	2.20	65.0%	1/2"	8-3/16" x 7-9/16"	Dbl. Shaft	Slv	11.8	G21-930	385.00
S88-351	RA1016	5-5/8"	1/6	208-230	1075	3	0.96	65.0%	1/2"	8-5/16" x 7-9/16"	Dbl. Shaft	Slv	11.1	G21-930	349.00
S83-130	RAL1026A	5-5/8"	1/4	115	1075	3	3.40	65.0%	1/2"	8-1/8" x 7-5/8"	Dbl. Shaft	Slv	20.4	G21-930	479.00
S88-204	RAL1024	5-5/8"	1/4	115	1625	3	3.40	65.0%	1/2"	7-15/16" x 7-9/16"	Dbl. Shaft	Slv	12.5	G21-930	505.00
S88-223	RA1026	5-5/8"	1/4	208-230	1075	3	1.50	66.2%	1/2"	7-15/16" x 7-9/16"	Dbl. Shaft	Slv	13.1	G21-930	439.00
S88-205	RA1024	5-5/8"	1/4	208-230	1625	3	1.90	65.0%	1/2"	7-15/16" x 7-9/16"	Dbl. Shaft	Slv	12.8	G21-930	515.00
S88-353	RAL1036	5-5/8"	1/3	115	1075	3	5.00	65.0%	1/2"	8-1/6" x 6-13/16"	Dbl. Shaft	Slv	17.6	G21-930	439.00
S88-206	RAL1034	5-5/8"	1/3	115	1625	3	4.00	65.0%	1/2"	7-11/16" x 7-9/16"	Dbl. Shaft	Slv	13.8	G21-930	555.00
S88-224	RA1036	5-5/8"	1/3	208-230	1075	3	1.90	68.0%	1/2"	8-3/16" x 6-13/16"	Dbl. Shaft	Slv	15.7	G21-930	469.00
S88-207	RA1034	5-5/8"	1/3	208-230	1625	3	2.00	65.0%	1/2"	7-11/16" x 7-9/16"	Dbl. Shaft	Slv	14.5	G21-930	529.00
S88-211	RAL1056	5-5/8"	1/2	115	1075	3	7.6	65.0%	1/2"	7-7/16" x 6-13/16"	Dbl. Shaft	Slv	19.7	G21-891	535.00
S88-208	RAL1054	5-5/8"	1/2	115	1625	3	6.00	65.0%	1/2"	7-15/16" x 6-13/16"	Dbl. Shaft	Slv	16.3	G21-930	609.00
S88-212	RA1056	5-5/8"	1/2	208-230	1075	3	2.70	67.3%	1/2"	7-11/16" x 6-13/16"	Dbl. Shaft	Slv	18.4	G21-933	545.00
S88-209	RA1054	5-5/8"	1/2	208-230	1625	3	3.20	65.0%	1/2"	7-15/16" x 6-13/16"	Dbl. Shaft	Slv	17.0	G21-930	585.00
S89-047	RAL1076	5-5/8"	3/4	115	1075	3	8.20	65.0%	1/2"	7-7/16" x 6-13/16"	Dbl. Shaft	Slv	20.0	G21-897	675.00
S88-213	RA1076	5-5/8"	3/4	208-230	1075	3	3.60	67.9%	1/2"	7-7/16" x 6-13/16"	Dbl. Shaft	Slv	19.1	G21-933	685.00
S88-210	RA1074	5-5/8"	3/4	208-230	1625	3	3.80	65.0%	1/2"	7-7/16" x 6-13/16"	Dbl. Shaft	Slv	20.4	G21-933	679.00



Double Shaft, 277 Volt Motors

PSC, 48 Frame, Open Air Over

Applications:

- Hotel and motel package air conditioners

Features:

- 3-speed, single-phase, sleeve bearing
- Enclosed opposite lead end, lead end open

- 1-1/2" extended tie bolts lead end with hub opposite lead end to accept resilient ring adapter kits
- Capacitor not included
- Automatic thermal protection

Order #	Mfg. #	Diam.	HP	Volts	RPM	Speeds	F/L Amps	Efficiency	Shaft Diam.	Shaft Length	Rot.	"A" Dim.	Bearing Type	Wt. Lbs.	Capacitor To Match	Each
S88-447	7RA1016	5-5/8"	1/6	277	1075	3	0.80	65.0%	1/2"	8-3/16" x 7-11/16"	Dbl. Shaft	3-11/16"	Slv	11.7	G21-930	659.00
S88-448	7RA1026	5-5/8"	1/4	277	1075	3	1.30	65.0%	1/2"	8-11/16" x 7-11/16"	Dbl. Shaft	3-13/16"	Slv	12.8	G21-930	645.00
S88-449	7RA1036	5-5/8"	1/3	277	1075	3	1.90	65.0%	1/2"	7-13/16" x 7-5/16"	Dbl. Shaft	4-7/16"	Slv	15.4	G21-933	689.00